

PUSH-BUTTON

Saniflow E05



E05



E05C



E05CS



E05B

General description

- Saniflow® push-button hand dryer is the rotating nozzle dryer that is most widely used in the world, regardless of the location to be fitted.
- These machines also feature easy maintenance, low noise levels and a high level of user safety. Together with an accurate design of components, SANIFLOW dryers boast the most powerful airflow in the world, which, combined with a comfortable drying temperature, reduces drying times to a minimum.
- Available in a 1,5 mm. thick steel cover, white or black finished or in a 1,5 mm. thick stainless steel cover bright or satin finished, this hand dryer is ideal for Heavy traffic Bathrooms.
- Thus, these are proven models with a long durability and complete reliability, with anti-vandalism features and designed to be installed in high traffic of people such as airports, large hotels, sport centers, large recreational areas and large official organizations, among others.
- Optionally, it can incorporate odor-neutralizing balls (code RFCB001) that aromatize and deodorize the environment through their soft fragrance.


Components & materials

- **E05:** 1,5 mm. thick steel cover, white finished.
- **E05B:** 1,5 mm. thick steel cover, black finished.
- **E05C:** 1,5 mm. thick stainless steel cover, bright finish.
- **E05CS:** 1,5 mm. thick stainless steel cover, satin finish.
- **MOTOR:** universal brush motor, 5.500 rpm, F class, which includes a safety thermal cut-off.
- **COVER:** one-piece fixed to the base by means of 2 vandal-proof lock screws and lock with special Saniflow ® wrench.
- **BASE PLATE:** made of aluminium, 3 mm thick, with 4 Ø 8 mm holes for wall mounting.
- **FAN SCROLL:** made of fire resistant plastic UL 94-VO.
- **FAN WHEEL:** centrifugal double symmetrical inlet fan wheel made of aluminium.
- **HEATING ELEMENT:** made with waved wire NiCr on a mica frame that incorporates a thermal cut-off.
- **NOZZLE:** 360° Nozzle in chrome plated Zamak.
- **PUSH-BUTTON:** made of chrome-plated zamak, that activates an electronic timer with a 35 seconds cycle.
- **SILENT BLOCKS:** 4 units assembled in the rear part of the base plate to eliminate vibrations.
- **ODOR-NEUTRALIZING BALLS:** code RFCB001 for a cleaner and more pleasant atmosphere in the bathroom (optional).

Technical Specifications

Voltage	220- 240 V
Frequency	50/60 Hz
Electrical Isolation	Class I
Total power	2,250 W
Consumption	10 A
Motor power	250 W
Rpm	5,500
Heating element power	2,000 W
Dimensions	245x276x214 mm
Weight	4,65 Kg
Cover thickness	1.5 mm
Drying time	29 sec.
Air velocity	100 Km/h
Air temperature (10 cm distance/21°C)	50 °C
Sound pressure (at 2m)	68 dBA
Protection rating	IP23

Dimensions:




Dim. +/-4%

Operation

Press the push-button to initiate the drying process, place the hands under the rotating nozzle into the air outlet and rub them together. The dryer will go on with no interruption for 35 seconds.

Mounting

Recommended heights distance from the floor



Certificates and Qualifications



Mediclinics, S.A., reserves the right to make changes and/or modifications to the products and their specifications without prior notice.
 Review 10-21 © mediclinics S.A.

